



**ADHERE BONDS**  
The Versatile Construction Chemicals



## ADHEREX-34

MULTIPURPOSE EPOXY ADHESIVE

### Adherex-34

Multipurpose Epoxy Adhesive is a high strength structural adhesive used to bond and assemble sub-components to form rigid final structures. The high viscosity provides excellent gap filling characteristics that strengthen loose fitting joints and panels. It forms tough durable bonds to composites, SMC, foam, wood, fiber glass, many metals, and even common construction materials, It is easy to use with its 1:1 mix ratio, and cures relatively quickly, developing sufficient "green strength" to allow bonded items to be removed from the holding fixtures and handled within a few hours. The cured material has excellent strength, as well as, good resistance to weak acids, moisture and weather.

- Special Adhesive to bond anything and everything.
- Free from Laborious Work
- Saves time
- Eco Environ friendly
- Withstand heavy loads.

**ADHEREX – 34** is a two pack high built Epoxy Adhesive, Conforming to Global Standards with high Bonding & Sealing strength. Very ideal for fixing sealing vertically and horizontally with minimum labour and effort. Highly recommended for bath rooms, water tanks, swimming pools and roof top applications.

### Features:

- High bonding strength
- Mild Acid, Alkali resistant
- Highly cost effective for heavy application
- 100% waterproof
- Fire retardant quality Wet Surface curing property
- Easy to apply

### Note:

Whilst any information and / or specification contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendation or suggestions made by us, our representatives, agents or distributors as the conditions of use of any labour involved are beyond our control.

### Application Data:

Mixing Ratio	1 : 1	
Colour after mixing		Grey
Density after mixing gm/cc	1.4	

### Technical Data:

Consistency	Component A
Colour	Grey
Density g/cm <sup>2</sup>	1.8
Dry Solid content %	100
Thick paste	Component B
Colour	Beige
Density g/cm <sup>2</sup>	1.4
Dry Solid content %	100

### Pot Life:

- 45 minutes
- Open time 60 mints
- Set to light foot traffic 10-12 hours
- Ready to Use-after 2days

### Packing:

- 2, 4, 10kgs

Adhere Bonds  
Coats Pvt Ltd

